

Alligator® Spiral Lace Selection Chart

FASTENER SIZE	APPROX. BELT THICKNESS RANGE		MINIMUM PULLY/ NOSE BAR		APPROX. OPERATING TENSION		MAX. OPERATING TEMPERATURE		APPROX. PIN DIAMETER	
	in.	mm	in.	mm	P.L.W.	kN/M	Degrees F	Degrees C	in.	mm
ASL60/ASL160	1/32 - 1/8	.8 - 3.2	1/2	12.7	50	8.7	300	150	.035	.9
ASL90/ASL190	1/8 - 3/16	3.2 - 4.6	5/8	15.3	50	8.7	300	150	.047	1.2
ASL80H	Up to 1/4	Up to 6.4	5/8	15.3	50	8.7	392	200	.047	1.2

Alligator® Spiral Lace

LENGTH		ORDERING NUMBER	ITEM CODE
Feet	Meters		
WHITE - SINGLE WEB			
10	3	ASL50/3	19460
10	3	ASL60/3	19461
33	10	ASL60/10	19462
100	30	ASL60/30	19463
10	3	ASL90/3	19466
33	10	ASL90/10	19467
100	30	ASL90/30	19468
10	3	ASL160/3	19483
10	3	ASL190/3	19484
WHITE - DOUBLE WEB			
10	3	ASL60D/3	19476
33	10	ASL60D/10	19477
100	30	ASL60D/30	19478
10	3	ASL90D/3	19479
33	10	ASL90D/10	19480
100	30	ASL90D/30	19481
10	3	ASL100D/3	19488
TAN - DOUBLE WEB - HIGH HEAT			
10	3	ASL80H/3	19470

LENGTH		ORDERING NUMBER	ITEM CODE
Feet	Meters		
WHITE - SINGLE WEB			
10	3	ASLB60/3	19486
10	3	ASLB90/3	19485
100	30	ASLB90/30	19491
BLACK - DOUBLE WEB			
10	3	ASLB90D/3	19489
33	10	ASLB90D/10	19480

Leader Pins

Note: Custom lengths available.

05200	POLYD35X15FT-W/3 FT	(15-foot pin with 3-foot leader)
05201	POLYD47X15FT-W/3 FT	(15-foot pin with 3-foot leader)

Replacement

Hinge Pins - Coils

ORDERING NUMBER	ITEM CODE
ASLHP60	19473
ASLHP90	19474
ASLHP80	19475