



## Dunham Rubber & Belting Corporation

682 Commerce Parkway West Drive, Greenwood, IN 46143

**Toll Free:** 800.876.5340

**Tel:** 317.888.3002

**Fax:** 317.888.2335

**Email:** [mail@dunhamrubber.com](mailto:mail@dunhamrubber.com)

# Aeroquip FC558 Refrigeration/Air Conditioning

5 Items Available

---

## Construction

- Butyl rubber tube
- High tensile steel wire reinforcement
- Synthetic rubber insulation layer
- Polyester braid cover
- SAE 100R5 reusable fittings

## Operating Temperature Range

-40°F to +250°F (-40°C to +121°C)

## R-134a Effusion

5.5 lbs/ft<sup>2</sup>/yr at 176°F

## Moisture Ingression

0.80gm/in.<sup>2</sup>/yr

## Benefits

- Excellent effusion resistance
- Extended service life
- Maximum resistance to moisture ingression
- Superior abrasion resistance
- Field attachable fittings



## View items

Item #	Hose I.D.	Hose O.D.	Max. Operating Pressure	Min. Burst Pressure	Min. Bend Radius
<a href="#">FC558-10</a>	0.50 inches	0.92 inches	500 psi	2500 psi	5.50 Inch
<a href="#">FC558-12</a>	0.62 inches	1.06 inches	500 psi	2500 psi	6.50 Inch
<a href="#">FC558-16</a>	0.88 inches	1.24 inches	500 psi	2500 psi	7.38 Inch
<a href="#">FC558-20</a>	1.12 inches	1.51 inches	500 psi	2500 psi	9.00 Inch
<a href="#">FC558-24</a>	1.38 inches	1.75 inches	500 psi	2500 psi	10.50 Inch