

NOVITOOL® AERO® Splice Press

Aero® Ordering Information

Belt Width		Ordering Number	Item Code
in	mm		
24	625	AERO-625 - Dunham	09451
36	925	AERO-925 - Dunham	09452
48	1225	AERO-1225 - Dunham	09453
60	1525	AERO-1525 - Dunham	09454
72	1835	AERO-1835 - Dunham	09455
84	2135	AERO-2135 - Dunham	09456



Aero® Tool Specifications

Specifications	Aero® 625	Aero® 925	Aero® 1225	Aero® 1525	Aero® 1835	Aero® 2135
Effective splice length	24.6" / 625 mm	36.4" / 925 mm	48.2" / 1225 mm	60" / 1525 mm	72.2" / 1835 mm	84" / 2135 mm
Effective splice width	6" / 150 mm	6" / 150 mm	6" / 150 mm	6" / 150 mm	6" / 150 mm	6" / 150 mm
Upper weight	40.2 lbs (18.23 kg)	54.2 lbs (24.6 kg)	67 lbs (30.4 kg)	96.2 lbs (43.6 kg)	110.2 lbs (50 kg)	124.8 lbs (56.6 kg)
Lower weight	45.8 lbs (20.8 kg)	59.1 lbs (26.8 kg)	72.9 lbs (33.1 kg)	100.8 lbs (45.7 kg)	115.9 lbs (52.6 kg)	132.3 lbs (60 kg)
Total weight	87.9 lbs (39.9 kg)	116.2 lbs (52.7 kg)	143.7 lbs (65.2 kg)	201.6 lbs (91.5 kg)	231.7 lbs (105 kg)	263.2 lbs (119.4 kg)
Length	32.5" / 825 mm	44.3" / 1125 mm	56.1" / 1425 mm	67.9" / 1725 mm	79.7" / 2025 mm	91.5" / 2325 mm
Height upper part	6.3" / 160 mm	6.3" / 160 mm	6.3" / 160 mm	7.3" / 185 mm	7.3" / 185 mm	7.3" / 185 mm
Height lower part	3.3" / 85 mm	3.3" / 85 mm	3.3" / 85 mm	5.5" / 140 mm	5.5" / 140 mm	5.5" / 140 mm
Overall height	9.6" / 245 mm	9.6" / 245 mm	9.6" / 245 mm	12.8" / 325 mm	12.8" / 325 mm	12.8" / 325 mm
Max. pressure	28 psi / 2 bar	28 psi / 2 bar	28 psi / 2 bar	28 psi / 2 bar	28 psi / 2 bar	28 psi / 2 bar
Max. temperature	392 °F / 200 °C	392 °F / 200 °C	392 °F / 200 °C	392 °F / 200 °C	392 °F / 200 °C	392 °F / 200 °C
Temperature ratings	-20C to +40C Operating -25C to +50C Storage	-20C to +40C Operating -25C to +50C Storage	-20C to +40C Operating -25C to +50C Storage	-20C to +40C Operating -25C to +50C Storage	-20C to +40C Operating -25C to +50C Storage	-20C to +40C Operating -25C to +50C Storage
Transport dimensions	41" x 18" x 19.4" 1024 mm x 456 mm x 492 mm	52" x 18" x 19.4" 1324 mm x 456 mm x 492 mm	64" x 18" x 19.4" 1624 mm x 456 mm x 492 mm	75.7" x 18" x 20.8" 1924 mm x 456 mm x 527 mm	87.6" x 18" x 20.8" 2224 mm x 456 mm x 527 mm	99.4" x 18" x 20.8" 2524 mm x 456 mm x 527 mm

Aero® Power Compatibility and Power Cord Specifications

Power	Country	625	925	1225	1525	1835	2135	Plug End	Ordering Number	Item Code
1ph 110V, 15A	USA	R	N/A	N/A	N/A	N/A	N/A		AERO-G3-CBL-110V1PH-N5-15	09006
1ph 110V, 20A	USA	R	R	R	N/A	N/A	N/A		AERO-G3-CBL-110V1PH-N5-20	09007
1ph 110V, 16A	UK	R	R	R	N/A	N/A	N/A		AERO-G3-CBL-110V1PH-IEC60309	09017
1ph 230V, 10A	AUS	F	R	R	N/A	N/A	N/A		AERO-G3-CBL-230V1PH-3112-10	09008
1ph 230V, 13A	UK	F	R	R	R	N/A	N/A		AERO-G3-CBL-230V1PH-BS1363-13	09018
1ph 230V, 16A	EUR	F	F	R	R	R	R		AERO-G3-CBL-230V1PH-ESHUK0-16	09009
1ph 230V, 30A	USA	F	F	F	F	R	R		AERO-G3-CBL-230V1PH-NL6-30	09010
3ph 230V, 20A	USA	F	F	F	R	R	R		AERO-G3-CBL-230V3PH-NL15-20	09011
3ph 230V, 30A	USA	F	F	F	F	R	R		AERO-G3-CBL-230V3PH-L15-30	09020
3ph 400V +N	EUR	F	F	F	F	F	F		AERO-G3-CBL-400V3PH+N-IEC60309	09012
3ph 400V no N	EUR	N/A	N/A	N/A	F	F	F		AERO-G3-CBL-400V3PH-N-IEC60309	09013
3ph 460V	USA	N/A	N/A	N/A	F	F	F		AERO-G3-CBL-460V3PH-L16-30	09014

(F= full power operation, R= reduced power operation)



Dunham Rubber & Belting Corporation • 682 Commerce Parkway West Drive
Greenwood, IN 46143 • (800) 876-5340 • E-mail: mail@dunhamrubber.com